

FAE140 ASPHALT PAVER



Fa Engineering srl si riserva di modificare le caratteristiche tecniche.

SPECIFICATION

Brand	CAT
Engine	C2.2 Stage V
Output	55 Kw
Electrics	14 Volt / Alternator 85 A
DPF	Filter DPF
Certification	EU 2016/1628 & EPA
Reference	SAE J-1995

MATERIAL HOPPER

Hopper capacity	3,2 Mc
Hopper width	3050 mm
Truck discharge high	530 mm

TANK CAPACITY

Fuel	65 lt
Hydraulic Oil	90 lt

TRASMISSION

Track Base	1530mm
Track Pad Width	200mm
Trasmissione Type	Hydrostatic 2x2 speed motor
Speeds 1st gear (Work)	0-22 mt/mim
Speeds 2st gear (Travel)	0-3.5 km/hr
Brakes	Service= Hydrostatic Park= Multidisc negative
Steering Type	Electric
Turning Radius	Inside 0.70 mtrs
Ground pressure	0 .75kg/cm2
Ground Clearance	190mm

WEIGHTS

Operating weight	4950 kg
------------------	---------

SCREED PAVING RANGE

Layer thickness	200 mm
Hydraulically extendable	1400 mm- 2600mm
Maximum h/extendable	2600mm-3400mm
Model	SCR V26

SCREED HEATING

Generator-Electric	13 Kw - 240 Volt - 50 Hz
--------------------	--------------------------

Independent section screed heating adjustable controller
Visual temperature and section selection (optional)

CONVEYOR & AUGER

Conveyor type	1 x reversible
Conveyor control	on/off
Conveyor performance	Man/auto up to 32 mtr/min
Auger Type	2x independent reversible
Auger control	proportional
Auger performance	82 rpm
Auger diameter	260 mm

OPTIONAL EQUIPMENT

Push Roller oscillating
Kit Screed extensions to 2600-3400mm
Digital display control management connect
Grade/Slope Control-analogue or digital
Adjustment Hydraulic Auger
Proportional Sonic Auger Control
Auxiliary Service 1 Kw - 240 Volt
Canopy
Full Led 8 lamps

29/08/2022

FA ENGINEERING SRL VIA DELL'ARTIGIANATO 222 - CORBOLA (RO)